

# PATRIOT SERIES - HOT WATER

INDUSTRIAL

The Patriot, designed for versatility, offers both portability and stationary use. It is engineered to deliver a superior clean tailored to your needs. The units are equipped with extended fuel tanks

## UNIT INCLUDES

- Hose
- Lance
- Trigger gun
- Nozzles: 15°, 25°, and 40°
- Engine oil 10W-30

## LIMITED WARRANTY

All Units 10yr Frame, 5yr Pump, 3yr Engine

## FEATURES

- 1750 RPM slow speed
- V-twin horizontal engine with key-start (battery not included)
- NEMA 4X electrical enclosure with burner on/off rocker switch and hour meter
- Corrosion-resistant stainless steel coil cover
- Isolated pump & engine plate with vibration dampeners
- 3.4 kw generator with one 120V duplex outlet
- 120V burner system
- Burner fuels: No. 1/No. 2 diesel or kerosene
- 1/2" Schedule 80 horizontal coil



65013



MODEL #	PART #	PRESSURE	FLOW	ENGINE	PUMP   DRIVE	GAS TANK	DIESEL TANK	PRODUCT WEIGHT
DPT3080251EAC <sup>1</sup>	65013	3000 PSI	8.0 GPM	HONDA® GX690* w/Key-start	General Pump®   Belt	15 gal.	15 gal.	1050 lbs.
DPT3080151EAC <sup>1</sup>	65184	3000 PSI	8.0 GPM	CRX® 680* w/Key-start	General Pump®   Belt	15 gal.	15 gal.	1050 lbs.
DPT3080241EAC <sup>1</sup>	65366	3000 PSI	8.0 GPM	Vanguard® 23HP* w/Key-start	UDOR®   Belt	15 gal.	15 gal.	1050 lbs.
DPT3080141EAC <sup>1</sup>	65367	3000 PSI	8.0 GPM	CRX® 750* w/Key-start	UDOR®   Belt	15 gal.	15 gal.	1050 lbs.
DPT3080341EAC <sup>1</sup>	65368	3000 PSI	8.0 GPM	HONDA® GX690* w/Key-start	UDOR®   Belt	15 gal.	15 gal.	1050 lbs.

## PUMPS

### General Pump® Industrial Triplex

- 1750 RPM slow speed
- Thermal relief valve
- Forged brass manifold
- Ceramic-coated plunger sleeves
- External unloader with bypass hose

### UDOR® Industrial Triplex Pump

- Forged brass manifold
- Thermal relief valve
- Ceramic-coated plunger sleeves
- External unloader with bypass hose

## FRAME

- Heavy-duty 1-1/2" round tubular steel design
- Powder-coated for corrosion resistance
- Removable feet for forklift capabilities and alternative mounting options

## HOSE

- 3/8" x 50' steel-braided Armor Hose®

## NOZZLES

- Quick-connect nozzles for a variety of cleaning applications

## ENGINES LOW OIL SHUTDOWN

ENGINE	DISPLACEMENT
CRX® 680	679cc
CRX® 750	750cc
HONDA® GX690	688cc
VANGUARD® 23HP	627cc

## DIMENSIONS

All Units L 47" x W 43" x H 39"

<sup>1</sup> - This product is 49-State/EPA-Compliant. Not for sale in the state of California.

\* - Indicates engine is equipped with low-oil shutdown technology. Refer to page 34 for additional information.