

STREAMLINER SERIES - HOT WATER

INDUSTRIAL

This potent mobile washing system is ingeniously designed to be compact, allowing it to comfortably fit within the confines of a transit van or truck bed, and effortlessly pass through a 36" doorway.

UNIT INCLUDES

- Hose
- Lance
- Trigger gun
- Nozzles: 15°, 25°, and 40°
- Engine oil 10W-30
- Downstream injector

LIMITED WARRANTY

All Units 10yr Frame, 5yr Pump, 3yr Engine

FEATURES

- 1750 RPM slow speed
- CRX®, HONDA®, VANGUARD® key-start engines (battery not included)
- Burner on/off rocker switch and hour meter
- High-temperature safety switch
- Isolated pump & engine plate with vibration dampeners
- 3.4 kw generator with two 120V outlets
- 120V burner system
- Wheel brake system
- Burner fuels: No. 1/No. 2 diesel or kerosene
- 1/2" Schedule 80 horizontal coil
- Large-capacity fuel tank



65016



MODEL #	PART #	PRESSURE	FLOW	ENGINE	PUMP	GAS TANK	DIESEL TANK	PRODUCT WEIGHT
DSL4040253EDC1 ¹	65016	4000 PSI	4.0 GPM	HONDA® GX390* w/Key-start	General Pump® Gear	5.0 gal.	10.0 gal.	450 lbs.
DSL4040242EDC1 ¹	65361	4000 PSI	4.0 GPM	HONDA® GX390* w/Key-start	UDOR® Direct	5.0 gal.	10.0 gal.	450 lbs.
DSL4040342EDC1 ^{1**}	65362	4000 PSI	4.0 GPM	VANGUARD® 470cc* w/Key-start	UDOR® Direct	5.0 gal.	10.0 gal.	470 lbs.
DSL4040142EDC1 ¹	65363	4000 PSI	4.0 GPM	CRX® 420* w/Key-start	UDOR® Direct	5.0 gal.	10.0 gal.	450 lbs.
DSL4040143EDC1 ¹	65364	4000 PSI	4.0 GPM	CRX® 420* w/Key-start	UDOR® Gear	5.0 gal.	10.0 gal.	450 lbs.
DSL4040343EDC1 ^{1**}	65365	4000 PSI	4.0 GPM	VANGUARD® 470cc* w/Key-start	UDOR® Gear	5.0 gal.	10.0 gal.	470 lbs.

PUMPS

General Pump® Industrial Triplex

- Thermal relief valve
- Forged brass manifold
- Ceramic-coated plunger sleeves
- External unloader with bypass hose

UDOR® Industrial Triplex Pump

- Forged brass manifold
- Thermal relief valve
- Ceramic-coated plunger sleeves
- External unloader with bypass hose

FRAME

- Heavy-duty 1-1/2" round tubular steel design
- Powder-coated for corrosion resistance

HOSE

- 3/8" x 50' steel-braided Armor Hose®

NOZZLES

- Quick-connect nozzles for a variety of cleaning applications

ENGINES LOW OIL SHUTDOWN

ENGINE	DISPLACEMENT
CRX® 420	420cc
HONDA® GX390	389cc
VANGUARD® 470cc	470cc

DIMENSIONS

All Units L 50" x W 32" x H 52"

¹ - This product is 49-State/EPA-Compliant. Not for sale in the state of California.

* - Indicates engine is equipped with low-oil shutdown technology. Refer to page 34 for additional information.

** - Battery not included.